

HOTLINE

LED Tracklight 1100 - 3075 Lumens





























HOTLINE LED Tracklight 1165 - 3370 Lumens

Compact and stylish with multiple beam options

The Digilin Hotline series is a super compact LED tracklight with integral driver. The recessed COB LED and aluminium reflector produce excellent light output with reduced glare.


With 90 degree tilt and 360 degree pan plus glare and snoot ring attachments, the Hotline is perfect for commercial display, retail and residential applications.





Specifications

Version	Hotline 1200		Hotline 2500		Hotline 3300	
Colours	Warm	Neutral	Warm	Neutral	Warm	Neutral
Colour Temperature	3000K	4000K	3000K	4000K	3000K	4000K
Luminaire Lumens @ 64°/60°	1100	1130	2300	2360	3000	3075
Power	12 w		24.2w		31 w	
Current	350mA		700mA		900mA	
Voltage (Nominal)	34.5VDC		34.5VDC		34.5VDC	
Connected Load	15 w		28 W		36 w	
Weight	487g		870g		1230g	
Beam Options	15°, 24°, 35°					
Dimming Options	Mains Dimming, DALI dimming					
Typical CRI	90+ CRI					
MacAdams Ellipse	3 SDCM/MacAdam Steps					
Performance	L80 (15K) >90,000 Hrs 80% Lumen Maintenance (15K) @ 90,000 Hours					
Power Factor	>0.9					
Construction Material	Cast aluminium frame & heatsink					
Finish Colour	White, Black					
P Rating	IP20					
Mounting	3 Circuit Track Mount (Ceiling Recess and Surface Mount Kits Available)					
Accessories	Honeycomb Filter					

Dimensions







Ordering Codes



NOTE- Hotline range is manufactured to Digilin specifications by an international partner



LED Lighting
Fibre Optic Lighting
Lighting Control
Electronic Engineers



